

Customer requested information

Tone sets available in the DRC-1 and DS-32

Digit	ZVEI-P	ZVEI-ID	ZVEI-D	ZVEI-S	ZVEI-I	EIA	EEA	CCIR	Digit
0	2200	2200	2400	2400	2400	600	1981	1981	0
1	970	970	1060	1060	1060	741	1124	1124	1
2	1060	1060	1160	1160	1160	882	1197	1197	2
3	1160	1160	1270	1270	1270	1023	1275	1275	3
4	1270	1270	1400	1400	1400	1164	1358	1358	4
5	1400	1400	1530	1530	1530	1305	1446	1446	5
6	1530	1530	1670	1670	1670	1446	1540	1540	6
7	1670	1670	1830	1830	1830	1587	1640	1640	7
8	1830	1830	2000	2000	2000	1728	1747	1747	8
9	2000	2000	2200	2200	2200	1869	1860	1860	9
A	825	886	970	886	2800	2151	1055	2400	A
B	740	2800	810	810	810	2433	930	930	B
C	2600	2600	2800	740	970	2010	2247	2247	C
D	886	825	886	680	886	2292	991	991	D
E	2400	2400	2600	970	2600	459	2110	2110	E
	Hz	Hz	Hz	Hz	Hz	Hz	Hz	Hz	

The table above lists by tone set, the frequencies (integer numbers shown) generated by the DRC-1 and DS-32 for each digit and including alpha characters A to D. These were measured on an HP test set type 8920A in response to a customer request for this information.

This report dated 23rd June 03 and will appear as annex1 to the relevant product manuals.